

R 75 + PS 4,8 Combi



R 75 + PS 4,8 Combi

- Toepassing: Staaldak 0,70 t/m 0,88 mm
- Te verwerken met IT-19 of extender
- Kunststof tule Ø 75 mm
- Guardian S-punt schroef
- Torx-25 kop
- Enduroguard coating, 15 cycli
- Sintef approval 2516
- ETA approval 08/0285
- Verpakt in dozen, per 250 stuks

ARTIKELCODE	TULE/SCHROEF Ø MM X LENGTE MM	MAX. OPBOUWDIKTE
1412458	R75+PS/ISO040, 75 X 20 / 4,8 X 060	40mm
1412459	R75+PS/ISO050, 75 X 20 / 4,8 X 070	50mm
1412460	R75+PS/ISO060, 75 X 40 / 4,8 X 060	60mm
1412461	R75+PS/ISO070, 75 X 40 / 4,8 X 070	70mm
1412462	R75+PS/ISO080, 75 X 60 / 4,8 X 060	80mm
1412463	R75+PS/ISO090, 75 X 60 / 4,8 X 070	90mm
1412464	R75+PS/ISO100, 75 X 80 / 4,8 X 060	100mm
1412465	R75+PS/ISO110, 75 X 90 / 4,8 X 060	110mm
1412466	R75+PS/ISO120, 75 X 90 / 4,8 X 070	120mm
1412467	R75+PS/ISO130, 75 X 90 / 4,8 X 080	130mm
1412468	R75+PS/ISO140, 75 X 120 / 4,8 X 060	140mm
1412469	R75+PS/ISO150, 75 X 120 / 4,8 X 070	150mm
1412470	R75+PS/ISO160, 75 X 120 / 4,8 X 080	160mm
1412471	R75+PS/ISO170, 75 X 150 / 4,8 X 060	170mm
1412472	R75+PS/ISO180, 75 X 150 / 4,8 X 070	180mm
1412473	R75+PS/ISO190, 75 X 150 / 4,8 X 080	190mm
1412474	R75+PS/ISO200, 75 X 180 / 4,8 X 060	200mm
1412475	R75+PS/ISO210, 75 X 180 / 4,8 X 070	210mm
1412476	R75+PS/ISO220, 75 X 180 / 4,8 X 080	220mm
1412477	R75+PS/ISO230, 75 X 210 / 4,8 X 060	230mm
1412478	R75+PS/ISO240, 75 X 210 / 4,8 X 070	240mm
1412479	R75+PS/ISO250, 75 X 210 / 4,8 X 080	250mm
1412480	R75+PS/ISO260, 75 X 240 / 4,8 X 060	260mm
1412481	R75+PS/ISO270, 75 X 240 / 4,8 X 070	270mm
1412482	R75+PS/ISO280, 75 X 240 / 4,8 X 080	280mm
1412483	R75+PS/ISO290, 75 X 270 / 4,8 X 060	290mm
1412484	R75+PS/ISO300, 75 X 270 / 4,8 X 070	300mm
1412485	R75+PS/ISO310, 75 X 270 / 4,8 X 080	310mm
1412486	R75+PS/ISO320, 75 X 300 / 4,8 X 060	320mm
1412487	R75+PS/ISO330, 75 X 300 / 4,8 X 070	330mm
1412488	R75+PS/ISO340, 75 X 300 / 4,8 X 080	340mm
1412489	R75+PS/ISO350, 75 X 330 / 4,8 X 060	350mm
1412490	R75+PS/ISO360, 75 X 330 / 4,8 X 070	360mm
1412491	R75+PS/ISO370, 75 X 330 / 4,8 X 080	370mm
1412492	R75+PS/ISO380, 75 X 330 / 4,8 X 090	380mm
1412493	R75+PS/ISO390, 75 X 330 / 4,8 X 100	330mm
1412494	R75+PS/ISO400, 75 X 330 / 4,8 X 110	400mm

