

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Product name : Hypertectum Duoflex-Comp. A  
Product code : 160-2-1-A-ETS

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Main use category : Professional use  
Industrial/Professional use spec : For professional use only  
Use of the substance/mixture : Two component elastomeric, polyurethane based material, extended with purechemically polymerized black bitumen, for waterproofing any surface

**1.2.2. Uses advised against**

Restrictions on use : The product is not recommended for any industrial, professional or consumer use other than the identified uses above

**1.3. Details of the supplier of the safety data sheet**

ETS-Europe BVBA B.V.B.A.  
Herentalsebaan 406 / Unit D1 Kmo Doornboom  
B-2160 Wommelgem  
BELGIUM  
T +32 (0) 3-227-28-58 - F +32 (0) 3 475-16-66  
[info@ets-europe.be](mailto:info@ets-europe.be)

**1.4. Emergency telephone number**

Emergency number : poison center tel: 00 32 (0) 70 245 245

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Respiratory sensitisation, Category 1	H334
Specific target organ toxicity – Repeated exposure, Category 2	H373

Full text of H- and EUH-statements: see section 16

**Adverse physicochemical, human health and environmental effects**

No additional information available

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS08

Signal word (CLP) :

Danger

Contains :

Reaction mass of ethylbenzene and m-xylene and p-xylene, m-tolyldiene diisocyanate; toluene-diisocyanate

Hazard statements (CLP) :

H226 - Flammable liquid and vapour.  
H315 - Causes skin irritation.

# Hypertectum Duoflex-Comp. A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP)	: H319 - Causes serious eye irritation. H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. H373 - May cause damage to organs through prolonged or repeated exposure. P260 - Do not breathe vapours. P280 - Wear protective gloves, face protection, eye protection. P302+P352 - IF ON SKIN: Wash with plenty of water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271 - Use only outdoors or in a well-ventilated area. P501 - Dispose of contents to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH204 - Contains isocyanates. May produce an allergic reaction.
Extra phrases	: As from 24 August 2023 adequate training is required before industrial or professional use.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Reaction mass of ethylbenzene and m-xylene and p-xylene substance with a Community workplace exposure limit	EC-No.: 905-562-9 REACH-no: 01-2119488216-32	15 – 17	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
m-tolylidene diisocyanate; toluene-diisocyanate	CAS-No.: 26471-62-5 EC-No.: 247-722-4 EC Index-No.: 615-006-00-4 REACH-no: 01-2119454791-34-0001,-0006, -0007	< 0,5	Carc. 2, H351 Acute Tox. 2 (Inhalation), H330 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317 Aquatic Chronic 3, H412

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
m-tolylidene diisocyanate; toluene-diisocyanate	CAS-No.: 26471-62-5 EC-No.: 247-722-4 EC Index-No.: 615-006-00-4 REACH-no: 01-2119454791-34-0001,-0006, -0007	( 0,1 $\leq$ C $\leq$ 100) Resp. Sens. 1, H334

# Hypertectum Duoflex-Comp. A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest. Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Wash with plenty of water/... Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes damage to organs.
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.
Symptoms/effects after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

#### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

##### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

# Hypertectum Duoflex-Comp. A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.  
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing fume, vapours, spray.  
Hygiene measures : Wash hands thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical equipment.  
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container tightly closed.  
Incompatible products : water, amines and alcohol's.  
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

Reaction mass of ethylbenzene and m-xylene and p-xylene	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	221 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m <sup>3</sup>
IOEL STEL [ppm]	100 ppm

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

# Hypertectum Duoflex-Comp. A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.1.4. DNEL and PNEC

Reaction mass of ethylbenzene and m-xylene and p-xylene	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	442 mg/m <sup>3</sup>
Acute - local effects, inhalation	442 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	212 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	221 mg/m <sup>3</sup>
Long-term - local effects, inhalation	221 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	260 mg/m <sup>3</sup>
Acute - local effects, inhalation	260 mg/m <sup>3</sup>
Long-term - systemic effects, oral	12,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	65,3 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day
Long-term - local effects, inhalation	65,3 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	327 µg/L
PNEC aqua (marine water)	327 µg/L
PNEC aqua (intermittent, freshwater)	327 µg/L
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	12,46 mg/kg dwt
PNEC sediment (marine water)	12,46 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	2,31 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	6,58 mg/l
<b>m-tolylidene diisocyanate; toluene-diisocyanate (26471-62-5)</b>	
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	12,5 µg/L
PNEC aqua (marine water)	1,25 µg/L
PNEC aqua (intermittent, freshwater)	125 µg/L
<b>PNEC (Soil)</b>	
PNEC soil	> 1 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	> 1 mg/l

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

No additional information available

# Hypertectum Duoflex-Comp. A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses with side shields

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing. Personal protective equipment for the body and appropriate footwear should be selected depending on the task being performed and possible exposure

##### Hand protection:

Suitable materials for safety gloves (EN 374):

Butyl rubber, Nitrile rubber, neoprene rubber. For prolonged or repeated exposure, gloves of class 5 or higher are recommended (breakthrough time >240min according to EN374). For short time use, gloves of class 3 or higher are recommended (breakthrough time >60min according to EN374). The thickness of gloves should be >0.35mm in order to provide adequate protection for prolonged contact with the product.

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

If concentration of one or more substances present in the product exceeds the exposure limit, use respiratory protective device (refer to EN 529)

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

#### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Flammable liquid and vapour.
Explosive properties	: Not applicable, product is not explosive.
Oxidising properties	: Not applicable, product is not oxidising.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 42 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not applicable, product is solvent-based
pH solution	: Not applicable, product is solvent-based
Viscosity, kinematic	: > 20,5 mm <sup>2</sup> /s

# Hypertectum Duoflex-Comp. A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Viscosity, dynamic	: 1000 – 1500 cP
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 0,95 – 1 g/cm <sup>3</sup>
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

VOC content : 153 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of hazardous reactions

None under normal use.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

### 10.5. Incompatible materials

Strong acids. Strong bases. water, amines and alcohol's.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Reaction mass of ethylbenzene and m-xylene and p-xylene	
LD50 oral rat	3523 mg/kg
LD50 dermal rabbit	12126 mg/kg
LC50 Inhalation - Rat (Vapours)	27124 mg/l/4h

m-tolylidene diisocyanate; toluene-diisocyanate (26471-62-5)	
LC50 Inhalation - Rat [ppm]	66 ppm/1h

Skin corrosion/irritation : Causes skin irritation.  
pH: Not applicable, product is solvent-based

# Hypertectum Duoflex-Comp. A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable, product is solvent-based
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met

### Reaction mass of ethylbenzene and m-xylene and p-xylene

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

### m-tolylidene diisocyanate; toluene-diisocyanate (26471-62-5)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

### Reaction mass of ethylbenzene and m-xylene and p-xylene

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Aspiration hazard : Not classified  
Additional information : Based on available data, the classification criteria are not met

### Hypertectum Duoflex-Comp. A

Viscosity, kinematic	> 20,5 mm <sup>2</sup> /s
----------------------	---------------------------

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

### 11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

### Reaction mass of ethylbenzene and m-xylene and p-xylene

LC50 - Fish [1]	2,6 mg/l LC50 96h fish
-----------------	------------------------

NOEC chronic fish	1,3 mg/l
-------------------	----------

### m-tolylidene diisocyanate; toluene-diisocyanate (26471-62-5)

LC50 - Fish [1]	133 mg/l Total exposure duration: 96 hours
-----------------	--

### 12.2. Persistence and degradability

### Hypertectum Duoflex-Comp. A

Persistence and degradability	No available data.
-------------------------------	--------------------

# Hypertectum Duoflex-Comp. A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.3. Bioaccumulative potential

#### Hypertectum Duoflex-Comp. A

Bioaccumulative potential	No available data.
---------------------------	--------------------

#### Reaction mass of ethylbenzene and m-xylene and p-xylene

Bioconcentration factor (BCF REACH)	25,9
-------------------------------------	------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

Additional information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to a hazardous or special waste collection point.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10* - packaging containing residues of or contaminated by dangerous substances

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

### 14.1. UN number or ID number

UN-No. (ADR)	: UN 1139
UN-No. (IMDG)	: UN 1139
UN-No. (IATA)	: UN 1139
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: COATING SOLUTION
Proper Shipping Name (IMDG)	: COATING SOLUTION
Proper Shipping Name (IATA)	: Coating solution
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable
Transport document description (ADR)	: UN 1139 COATING SOLUTION ( NOT SUBJECT TO THE PROVISIONS OF ADR - The product is packed in receptacles of less than 450 litres capacity. - Exempted according to 2.2.3.1.5 (Viscous substance exemption)), 3, III, (D/E)

# Hypertectum Duoflex-Comp. A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Transport document description (IMDG)	: UN 1139 COATING SOLUTION ( NOT SUBJECT TO THE PROVISIONS OF IMDG CODE FOR THE MARKING, LABELLING AND TESTING OF PACKAGES IN CHAPTERS 4.1, 5.2, AND 6.1. - The product is packed in receptacles not exceeding 30 L capacity - The following statement shall be included in the transport document: "Transport in accordance with 2.3.2.5 of the IMDG Code." ), 3, III
Transport document description (IATA)	: UN 1139 Coating solution, 3, III

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR)	: 3
Danger labels (ADR)	: 3



#### IMDG

Transport hazard class(es) (IMDG)	: 3
Danger labels (IMDG)	: 3



#### IATA

Transport hazard class(es) (IATA)	: 3
Danger labels (IATA)	: 3



#### ADN

Transport hazard class(es) (ADN)	: Not applicable
----------------------------------	------------------

#### RID

Transport hazard class(es) (RID)	: Not applicable
----------------------------------	------------------

### 14.4. Packing group

Packing group (ADR)	: III
Packing group (IMDG)	: III
Packing group (IATA)	: III
Packing group (ADN)	: Not applicable
Packing group (RID)	: Not applicable

### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001

# Hypertectum Duoflex-Comp. A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Mixed packing provisions (ADR) : MP19  
Transport category (ADR) : 3  
Special provisions for carriage - Packages (ADR) : V12  
Special provisions for carriage - Operation (ADR) : S2  
Hazard identification number (Kemler No.) : 30  
Orange plates :



Tunnel restriction code (ADR) : D/E  
EAC code : •3YE

### Transport by sea

Special provisions (IMDG) : 955  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : P001, LP01  
IBC packing instructions (IMDG) : IBC03  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-E  
Stowage category (IMDG) : A  
Flash point (IMDG) :  
Properties and observations (IMDG) :

### Air transport

PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y344  
PCA limited quantity max net quantity (IATA) : 10L  
PCA packing instructions (IATA) : 355  
PCA max net quantity (IATA) : 60L  
CAO packing instructions (IATA) : 366  
CAO max net quantity (IATA) : 220L  
Special provisions (IATA) : A3  
ERG code (IATA) : 3L

### Inland waterway transport

No data available

### Rail transport

No data available

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no REACH substances with Annex XVII restrictions

##### REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances

##### REACH Candidate List (SVHC)

Contains no substance on the REACH candidate list

# Hypertectum Duoflex-Comp. A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

### POP Regulation (Persistent Organic Pollutants)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

### Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

### VOC Directive (2004/42)

VOC content : 153 g/l

### Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on drug precursors)

### 15.1.2. National regulations

#### Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).  
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

#### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed  
SZW-lijst van mutagene stoffen : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

#### Denmark

Class for fire hazard : Class II-1  
Store unit : 5 liter  
Classification remarks : R10 <H226;H315;H319;H334;H373>; Emergency management guidelines for the storage of flammable liquids must be followed  
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product  
Persons suffering from asthma or eczema and persons who have chronic lung diseases, skin or respiratory allergies to isocyanates should not work with the material  
The requirements from the Danish Working Environment Authorities regarding work with epoxy resins and isocyanates must be observed during use and disposal

#### Switzerland

Storage class (LK) : LK 3 - Flammable liquids

### 15.2. Chemical safety assessment

No data available

## SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.  
Other information : None.

# Hypertectum Duoflex-Comp. A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
EUH204	Contains isocyanates. May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.